

**Ministry of Higher Education
and Scientific Research
University of Diyala
College of Engineering**



BEHAVIOR OF STRESSES AND DEFORMATIONS FOR SOIL SURROUNDING TBM TUNNEL BY FINITE ELEMENT SIMULATION

**A Thesis Submitted to the Council of the College of
Engineering, University of Diyala in Partial Fulfillment
of the Requirements for the Degree of Master of Science
in Civil Engineering**

by

Halah Hashim Mohammed

Supervised by

Assist. Prof. Dr. Waad A. Zakaria

Assist. Prof. Dr. Qasim A. Mahdi

November, 2018

IRAQ

Rabi AL-Awal, 1440

بِسْمِ اللَّهِ الرَّحْمَنِ الرَّحِيمِ (١)

الْحَمْدُ لِلَّهِ رَبِّ الْعَالَمِينَ (٢) الرَّحْمَنِ

الرَّحِيمِ (٣) مَا لِكَ يَوْمَ الدِّينِ (٤) إِيَّاكَ

نَعْبُدُ وَإِيَّاكَ نَسْتَعِينُ (٥) اهْدِنَا الصِّرَاطَ

الْمُسْتَقِيمَ (٦) صِرَاطَ الَّذِينَ أَنْعَمْتَ عَلَيْهِمْ

غَيْرِ الْمَغْضُوبِ عَلَيْهِمْ وَلَا الضَّالِّينَ (٧)

صدق الله العظيم

سورة الفاتحة

COMMITTEE DECISION

We certify that we have read the thesis entitled **(Behavior of Stresses and Deformations for Soil Surrounding TBM Tunnel by Finite Element Simulation)** and we have examined the student **(Halah Hashim Mohammed)** in its content and what is related with it, and in our opinion it is adequate as a thesis for the Degree of Master of Science in Civil Engineering.

Examination Committee	Signature
Assist. Prof. Dr. Waad A. Zakaria (Supervisor)
Assist. Prof. Dr. Qasim A. Mahdi (Co-Supervisor)
Assist. Prof. Dr. Mohammed Y. Fattah (Chairman)
Assist. Prof. Dr. Safa Hussain Abid Awn (Member)
Assist. Prof. Dr. Hassan Obaid Abbas (Member)
Prof. Dr. Hafeth Ibrahim Naji (Head of Department)	

**The thesis was ratified at the Council of College of Engineering/
University of Diyala.**

Signature:

Name: Prof. Dr. Abdul Monem Abbas Karim

Dean of College of Engineering/ University of Diyala.

Date:

CERTIFICATION

We certify that the thesis entitled “**Behavior of Stresses and Deformations for Soil Surrounding TBM Tunnel by Finite Element Simulation**” was prepared by “**Halah Hashim Mohammed**” under my supervision at the Department of Civil Engineering-College of Engineering-Diyala University in a partial fulfillment of the Requirements for the Degree of **Master of Science in Civil Engineering**.

Signature:

Supervisor: Assist. Prof. Dr. Waad A. Zakaria

Date:

Signature:

Co-Supervisor: Assist. Prof. Dr. Qasim A. Mahdi

Date:

In view of the available recommendation, I forward this thesis for debate by the examining committee.

Signature:

Name: Assist. Prof. Dr. Hafeth Ibrahim Naji

Chairman of the Department of Civil Engineering.

Date:

Dedication

***I Wish to Dedicate My
Thesis to The Light of My Eyes
My Beloved Parents (My Mother
and Father)***

Halah Hashim Mohammed

2018

Acknowledgements

"In the name of Allah, the most beneficent, the most merciful".
First praise be to "Allah" who gave me the strength and health to
work and enable me to achieve this research

I would like to express my sincere thanks to my supervisor
Assist. Prof. Dr. Waad A. Zakaria and Assist. Prof. Dr. Qasem A.
Al-Janabe, for their supervisions, precious advices, technical
guidance, continuous encouragements, and giving generously of
their time when help was needed throughout the preparation of
my thesis. I am greatly indebted to them.

Appreciation and thanks are also extended to the all staff of
College of Engineering/ University of Diyala and especially Civil
Engineering department and to every person helped me to
complete my thesis.

Finally, I would like to express my love and respect to my
parents and My brothers, no word can express my gratitude to
them.

Halah Hashim Mohammed

2018

ABSTRACT

The increasing investment for the underground space such as the construction of the tunneling will part of the infrastructure development and exploitation of this space which becomes fundamental base in the development of large cities. In an urban environment, the tunneling induced ground loss is an essential matter to estimate ground movement during the excavation process. Therefore, an attempt has been made to study the settlement and behavior of stresses through tunnels construction by tunnel boring machine method (TBM) and their influences on the adjacent structures.

In this research study is carried out to predict of the behavior of the stresses and ground movement effect of applying a tunnel boring machine during the excavation process. A numerical model is built and developed to a tunnel project within the governorate of Diyala. For this purpose, two profiles of soil investigations are brought the first from Al-Shareef Al-Jadeed bridge project and second for new buildings of Diyala University project.

The main objective of this research is to study the behavior of stresses and determine the settlement in the area of study using a finite element method and to assess and the determination of extent the impact of a distance to move the mechanism of the drilling and advance into the soil. The model is run as three dimensional in both drained to sandy soil and undrained of clay soil of states with applied Mohr-Coulomb model.

Results are presented in terms of stress-depth curves. Those stresses are the vertical and horizontal, total and effective in addition to the pore water pressure. The changes in state of stresses compared to the in-site soil are put into consideration. Three vertical sections are chosen to study the TBM tunneling effects on surrounding soil. The first section ($x=0$) runs through center of the tunnel. Second section is located near lateral edge of the tunnel, while the third section is chosen more or less far

from the tunnel edge. The advance of TBM is reflected by stages through one to five. It is believed that the mentioned details of the analysis will provide full vision of stress change in the soil profile. The strains induced by the boring process are presented in different and simple methods. These methods reflected the soil movement and surface settlement of soil. The deflected shape of the tunnel is shown as well. Through running an axis-symmetric FE analysis, calculation results revealed that large changes in stresses take place in zones of soil near the tunnel boundaries. In other words, the close-near by soil is mostly affected by tunneling. These stress changes reduce as proceeded farther away from tunnel horizontally and seams to reach a negligible values for distances above 12m away tunnel edge.

All changes in the state of stress compared to the in-site soil depend on soil profile in site. The FE results also revealed that soil change in stress is more pronounced in the zone above tunnel than under it. It is believed that surrounding confinement plays a major role to that. The deflected soil shape shows that there is a vertical depression in the tunnel associated with lateral bulge. Maximum surface settlement recorded is 20mm in the upper soil region over tunnel which belongs the Al-Shareef Al-Jadeed bridge project and level off as gelling away horizontally from tunnel center.

Upon proceeding with drilling, soil movement vectors seem to run towards the tunnel. As in the case of stresses, it is maximum in zones near tunnel. And last but not least, this study provides soil engineering a good guide and through understanding how to avoid places of heavy engineering facilities upon passing by TBM tunnel near or under these structures. Every soil site has its own profile and should run a full FE analysis but the general trend of behavior is through to the same.

TABLE OF CONTENTS

Subject	page
Examination Committee Approval	
Dedication	
Acknowledgement	
Abstract	I
Table of Contents	III
List of Tables	V
List of Figures	VI
List of Notations	XI
Chapter One: Introduction	
1.1 Introduction.....	1
1.2 The Problem Statement of Research	3
1.3 The Objectives of the Research	3
1.4 Methodology	4
1.5 Thesis Layout	4
Chapter Two: Literature Review	
2.1 Introduction	1
2.2 Tunnel Definition	1
2.3 Notations used in Tunneling	3
2.4 Types of Tunnel Construction Method	5
2.4.1 The Drill and Blast Method	7
2.4.2 The New Austrian Tunneling Method	7
2.4.3 Cut and Cover Method	8
2.4.4 Box Jacking Method	11
2.4.5 Tunnel Boring Machine Method (TBM)	11
2.5 Types of Tunnel Boring Machine	13
2.5.1 Slurry Shield Tunnel Boring Machine	13
2.5.2 Earth Pressure Balance Machine	14
2.5.3 Variable Density Tunnel Boring Machine	18
2.6 Excavation	18
2.7 Review of Prediction Methods for Settlement Induced by Tunneling	19
2.7.1 Empirical Method	21
2.7.2 Analytical Method	24
2.7.3 Numerical Analysis Method	25
2.7.3.1 Two Dimension Finite Element Analysis 2D	26
2.7.3.2 Three Dimension Finite Element Analysis 3D	29
Chapter Three: Numerical Model of Tunnel (TBM)	35
3.1 Introduction	35
3.2 Finite Elements and Nodes	35
3.3 PLAXIS Program	37
3.4 The Methodology of the PLAXIS Program	38
3.5 Excavation Tunnel by Tunnel Boring Machine Modeling	39
3.6 Model Generation	39
3.6.1 Geometry	39
3.6.2 Graphical Input of Geometry Model	40
3.6.2.1 Boreholes (Defining of Soil Layers)	40

3.6.2.2 Structure Element (Defining of Tunnel Excavation)	41
3.6.3 Material Characterization	42
3.6.4 Modeling of material Behavior	42
3.6.5 Defining of Drainage Type	43
3.6.6 Defining The Boring Tunnel Mechanical (TBM), and Contraction in The Model	44
3.6.7 Defining Interface	45
3.6.8 Mesh Generation	45
3.6.9 Defining of Staged Construction for The Model	46
3.7 Calculation Methodology	48
3.8 Types of Analysis	48
3.9 Output of The Model	49
3.10 curves	49
3.11 How to Choose from Stress Points and Node Points	50
3.12 Sign Convention Aspects	51
3.13 Location of Study	52
3.14 Data Collection	52
3.14.1 Soil Investigation for AL-Shareef AL-jadeed bridge	52
3.14.2 Soil Investigation for New Building of Diyala University	53
3.15 Data Obtained out of Proposed Projects	53
3.15.1 AL-Shareef AL-Jadeed Bridge	53
3.15.2 The New Buildings of Diyala University	56
Chapter Four: RESULTS and DISUNION	59
4.1 Introduction	59
4.2 Distribution of Stresses Around the Tunnel	59
4.2.1 Distribution of Stresses for Case Study 1	59
4.2.1.1 Distribution of Stresses for Case Study 1 on Distance 12.5m	60
4.2.1.2 The Distribution of Stresses for Case Study 1 on Distance 26.5m	61
4.3 Settlement Due to Construction of Tunnel	80
4.3.1 Settlement Due to Construction of Tunnel for Case Study 1 on Distance 12.5m	81
4.3.1.2 Settlement Due to Construction of Tunnel for Case Study 1 on Direction 26.5m	81
4.2.2 Distribution of Stresses for Case Study 2	89
4.2.2.1 The Distribution of Stresses for Case Study 2 on Distance 12.5m	89
4.2.2.2 The Distribution of Stresses for Case Study 2 on Distance 26.5m	90
4.3.2.1 Settlement Due to Construction of Tunnel for Case Study 2 on Distance 12	109
4.3.2.2. Settlement Due to Construction of Tunnel for Case Study 1 on Direction 26.5m	109
Chapter Five: Conclusions and Recommendations	
5.1 Introduction	118
5.2 Conclusions	118
5.3 Recommendations	121
References	123
Appendix (A) Soil Investigation	A-1
Appendix (B) Tables and Figures of Results	B-2

LIST OF TABLES

Tables No.	Table Title	Page
2.1	Some Information About Well-Known Tunnels (Dimitrios Kolymbas 2005) ..	7
2.2	Some Tunnels Constructed as Subway System (Dimitrios Kolymbas 2005) ...	8
3.1	Concrete parameter of tunnel linings.	42
3.2	Material parameters of plate element representing of TBM	44
3.3	The number of correlation blows for borehole one	54
3.4	Soil parameters borehole one	55
3.5	The number of correlation blows for borehole two	55
3.6	Soil parameter soil for borehole two	55
3.7	The number of correlation blows for borehole seven	57
3.8	Soil parameters for borehole seven	57
3.9	The number of correlation blows for borehole eight	57
3.10	Soil parameters for borehole eight	58
3.11	The number of correlation blows for borehole nine	59
3.12	Soil parameters for borehole nine	59
3.13	The number of correlation blows for borehole ten	59
3.14	Soil parameters for borehole ten	59
4.1	The maximum percentage of the vertical total stress	67
4.2	The maximum percentage of the vertical effective stress.....	67
4.3	The maximum percentage of the pore water pressure	68
4.4	The maximum percentage of the horizontal total stress	70
4.5	The maximum percentage of the horizontal effective stress.....	71
4.6	The maximum percentage of the vertical total stress	74
4.7	The maximum percentage of the vertical effective stress	75
4.8	The maximum percentage of the pore water pressure	76
4.9	The maximum percentages of deviations for the horizontal total stresses	78
4.10	The maximum percentages of deviations for the horizontal effective stresses ...	79
4.11	Magnitude of maximum displacement in vertical direction of all phases ...	82
4.12	Magnitude of maximum displacement in horizontal direction of all phases	85
4.13	The maximum percentages of deviations for the vertical total stresses	94
4.14	The maximum percentages of deviations for the vertical effective stresses	95
4.15	The maximum percentages of deviations for the pore water pressure	96
4.16	The maximum percentages of deviations for the horizontal total stresses	98
4.17	The maximum percentages of deviations for the horizontal effective stresses ...	99
4.18	The maximum percentages of deviations for the vertical total stresses ...	102
4.19	The maximum percentages of deviations for the vertical effective stresses ...	103
4.20	The maximum percentages of deviations for the pore water pressure	104
4.21	The maximum percentages of deviations for the horizontal total stresses	105
4.22	The maximum percentages of deviations for the horizontal effective stresses ...	106
4.23	Magnitude of maximum displacement in vertical direction of all phases ...	110
4.24	Magnitude of maximum displacement in horizontal direction of all phases ...	112

LIST OF FIGURES

Figure. No	Figure of Title	Page
1.1	Tunnel boring machine elements	2
2.1	Terminology related to a tunnel cross-section (Chapman et al 2010)	8
2.2	Longitudinal sections of heading (Dimitrios Kolymbas 2005)	8
2.3	Typical shapes of cross sections of tunnel used for the construction (Seung Royal Kim2008)	9
2.4	The different types of tunnel construction method (Arshad and R. A. Abdullah2015)	10
2.5	The series of construction include the conventional bottom-up method (Hung and Parsons 2009)	10
2.6	The series of construction included in the conventional top-down method (Hung and Parsons 2009)	13
2.7	The cut-and-cover method of the typical cross section with a groundwater cut off sketch (Seung-Ryull Kim2008)	14
2.8	The composing of slurry TBM (EFNARC 2005)	17
2.9	The equipment's of the Earth Pressure Balance Machine (Maidl, B., M. Thewes 2014)	17
2.10	TBM process sequence for heading	19
2.11	The vectors of the ground movement around tunnels in the sand(a) and (b)clay	20
2.12	Properties of error function curve to represent cross-section settlement trough above tunnel after (peck 1969)	22
2.13	Typical Gaussian settlement curve	23
2.14	Total deformation vectors on the surface	27
2.15	Calculated vertical displacement of the underground at the commercial center... 28	
2.16	Surface settlement obtained from different approaches.pp30	
2.17	Layout of the proposed TBM model by Ngoc-Anh, Daniel, Pierpaolo and Irini Djeran (2013)	31
2.18	Geometrical configuration of stability model	33
2.19	Finite element mesh of deformation model	33
2.20	Geometry of shallow tunnel for (a) 2D model and (b) 3D model	34
2.21	Geometry of deep tunnel for (a) 2D model and (b) 3D model	34
3.1	Flowchart of Methodology of Research.	36
3.2	Local numbering and positioning of nodes (•) and integration points (x) of tetrahedral element shape. (Brinkgreve et al, 2013)	37
3.3	Display site of boreholes and soil layers for first project	40
3.4	Display site of boreholes and soil layers for second project	40
3.5	Finite element mesh of connectivity plot for: (a) of first project and (b) of second Project	46
3.6	Distribution of forces of TBM machine for the first phase	47
3.7	Distribution of forces of TBM machine for the second phase	48
4.1	Distribution of the vertical stresses of native soil	64
4.2	Distribution of the horizontal stresses of native soil	64
4.3	Displaying several sections taken of tunnel model at X-direction.....	66
4.4	Distribution of the vertical total stress during construction phases of tunnel at x=0 with find deviations	67

4.5	Distribution of the vertical effective stress during construction phases of tunnel at x=0 with find deviations	68
4.6	Distribution of the pore water pressure during construction phases of tunnel at x=0 with find deviations	69
4.7	Distribution of the horizontal total stress during construction phases of tunnel at x=0 with find deviations	71
4.8	Distribution of the horizontal effective stress during construction phases of tunnel at x=0 with find deviations	72
4.9	Distribution of the vertical total stress during construction phases of tunnel at x=5 with find deviations	75
4.10	Distribution of the vertical effective stress during construction phases of tunnel at x=5 with find deviations	76
4.11	Distribution of the pore water pressure during construction phases of tunnel at x=5 with find deviations	77
4.12	Distribution of the horizontal total stress during construction phases of tunnel at x=5 with find deviations	79
4.13	Distribution of the horizontal effective stress during construction phases of tunnel at x=5 with find deviations	79
4.14	Total displacement at the vertical direction of the first phase	84
4.15	Deformed shape of mesh at a vertical direction of the first phase	85
4.16	Total displacement at the vertical direction of the second phase	86
4.17	Deformed shape of mesh at the vertical direction of the second phase	86
4.18	Total displacement at the horizontal direction of the first phase	87
4.19	Deformed shape of mesh at the horizontal direction of the first phase	88
4.20	Total displacement at the horizontal direction of the second phase	88
4.21	Deformed shape of mesh at the horizontal direction of the first phase	89
4.22	Comparison between settlement during at different construction stages	90
4.23	Comparison settlement between different methods	90
4.24	Distribution of the vertical stresses for the native soil	92
4.25	Distribution of the horizontal stresses for the native soil	92
4.26	Displaying several sections taken of tunnel model at X-direction	93
4.27	Distribution of the vertical total stresses during construction phases of tunnel model at x=0	

95		
4.28	Distribution of the vertical effective stresses during construction phases of tunnel model at $x=0$	96
4.29	Distribution of the pore water pressure during construction phases of tunnel model at $x=0$	97
4.30	Distribution of the horizontal total stresses during construction phases of tunnel model at $x=0$	99
4.31	Distribution of the horizontal effective stresses during construction phases of tunnel model at $x=0$	100
4.32	Distribution of the vertical total stresses during construction phases of tunnel model at $x=5$	
102		
4.33	Distribution of the vertical effective stresses during construction phases of tunnel model at $x=5$	
103		
4.34	Distribution of the pore water pressure stresses during construction phases of tunnel model at $x=5$	
104		
4.35	Distribution of the horizontal total stresses during construction phases of tunnel model at $x=5$	
106		
4.36	Distribution of the horizontal effective stresses during construction phases of tunnel model at $x=5$	
107		
4.37	Total displacement at the vertical direction of the first phase	
111		
4.38	Deformed shape of mesh at a vertical direction of the first phase	
111		
4.39	Total displacement at the vertical direction of the second phase	
112		
4.40	Deformed shape of mesh at the vertical direction of the second phase	
112		
4.41	Total displacement at the horizontal direction of the first phase	114
4.42	Deformed shape of mesh at the horizontal direction of the first phase	
114		
4.43	Total displacement at the horizontal direction of the second phase	114
4.44	Deformed shape of mesh at the horizontal direction of the first phase	
115		
4.45	Comparison between settlement during at construction stages	116
4.46	Comparison settlement between different methods	116

List of Notations

C_c	Compression index
C_s	Swelling index
C_u	Undrained cohesion
C_v	Coefficient of consolidation
DS	Disturbed Sample
e_o	Initial void ratio
G_s	Specific Gravity
LL	Liquid limit
M_v	Coefficient of volume change
N.P	Non-Plastic
OCR	Over consolidation ratio
PI	Plasticity index
PL	Plastic limit
Q_u	Unconfined Compressive Strength
SPT	Standard Penetration test
S.S	Standard Penetration test Samples
US	Undisturbed Samples
UU	Unconsolidated undrained triaxial test
P_o	Effective overburden pressure
P_c	Reconsolidation stress
\emptyset	Angle of internal friction
W_c	Natural moisture content
γ_t	Total unit weight
γ_{wet}	Wet Unit Weight
γ_{dry}	Dry unit weight
MC	Mohr-Coulomb Model
CY	Strain-Hardening Model
LE	Linear Elastic Model

CHAPTER ONE

INTRODUCTION

1.1 Introduction

The growth of many cities has resulted in the need for exploitation of underground space. As urban cities space become more limited, the construction of structures such as tunnels is more efficient in infrastructure development and fundamental in the development of large cities. The first underground railway line was opened in 1863 London. After that over 100 cities worldwide were carried out underground transport systems and over 50% of them had subjected to development or expansion (**Hellawell et al., 2001**).

Tunnels usually are structures passing underground. The benefits of tunnels are improving connections and shorten lifelines between countries. There are many cross-sections commonly adopted for tunnels, such as circular sections, elliptical, and rectangular or box type tunnels. Tunnel can be drilled in all types of soil varying from the loose ground, such as sand, gravel, clay up to hardest rock (**Rasheed, 2006**).

The excavation indicates the removal of soil within certain specified limits, or for building purposes. The necessity of constructions for such structures in urban areas has led to the need for a safe and efficient method for the deep excavations without severely influencing the adjacent structures.

In recent years the excavation methods in soft soil have improved after tunnels have become economically more attractive in the urban environment (**Obaid, 2001**). For example, the tunnel boring machine method (TBM) have been widely utilized in tunnel construction, especially in soft ground where the most important purpose is to minimize the soil deformation, as shown in Figure (1.1)




Figure (1.1): Tunnel boring machine elements (**Obaid, 2001**).

The tunnel boring machine can be with a cross-section of the circular and rectangular shapes. The advantage of excavation methods of tunnels and the increasing need to avoid any disturbance at the surface through excavations (**Dimitrios Kolymbas, 2005**).

When underground space or a large span tunnel is drilled, there will be a disturbance in-situ stress field which induces movements of soil and then leads to the surface settlement. Surface deformation may cause serious damage to adjacent buildings. Tunnel construction and design require the use of appropriate technologies at all stages of a tunnel project with selecting a suitable excavation method (**Sharifzadeh, et al,2013**).

Ground movement of surface caused by the tunnel construction methods is an important matter in urban areas due to the excessive deformations which can trigger possible damage to surrounding roads and adjacent structures (**Yahya and Abdullah, 2014**).

The amount surface settlement may differ according to different construction methods used for different cross-sections of the tunnel which leads to different settlements. As a result, the construction methods have an

important influence on the ground surface settlements (**Sharifzadeh, et al., 2013**).

The stresses and the ground movement in surrounding soil induced by drilling tunneling depend not only on the soil mass properties and the stresses, but depend also on the type and stiffness of the lining of a tunnel (**Brown, et al., 1983**).

1.1 The Problem Statement of Research

Apart from the analysis and construction of tunnel and its interaction with the ground which becomes operation too complex as a result of the dependence of this interaction on the construction technology. In addition to a complex sequence of operations for different excavation methods, especially tunnel boring machine (TBM), such as excavation, front support, shield advancement, grouting of the annular void, along with the shield and grout consolidation, the determination of settlements in the surface is very significant in tunneling.

However, in geotechnical engineering, these deformations can be predicted with accuracy, apart from the appreciation of soil stability where large deformations of either excavation can lead to undesirable consequences such as damage to adjacent structures.

In order to predict the reliably of deformations and distribution of stresses using a numerical method, the finite element method (FEM) analysis has become a popular tool which can simulate construction stages for tunneling.

1.2 The Objectives of the Research

This study concentrates on the behavior of the stresses and settlement through the construction of the tunnel using tunnel boring machine with its advance into the different soil layers. The main aims of the study are:

1. To build the numerical model using the finite element method of the tunnel model under constructed buildings and simulate of the constructed stages by the (TBM).
2. To calculate and analyze the behavior of settlement and stress of the upper part of soil and down part of the soil for tunneling in addition to the soil around the face of the tunneling.
3. To predict the settlement of adjacent areas and determine safe areas during the advance of the TBM up to the final phase of the tunnel construction.

1.4. Methodology

To achieve the objects of this study, a research methodology is developed using the finite element method by model building for predicting the behavior of stresses and settlement during construction stages of the tunnel considering the various area of work necessary to perform and obtain the results. This methodology is summarized as follows:

1. A comprehensive review of the previous studies to identify the models which should be used to simulate ground movement induce by tunneling through simulation of the tunnel boring machine operations and the important parameters for the work of this simulation.
2. Data collection which are utilized to construct the model by using finite element method.
3. Data obtained to match with the conditions of the study area and requirements of the model.
4. Simulating method of the tunnel construction. As a result of this simulation, the settlement of the adjacent structures can be predicted that induced by the tunnel and determine safe zones.
5. Analysis for input parameters of the numerical model.

1.5 Thesis Layout

The scope of this thesis consists of five chapters. Chapter one presents a general introduction and information about tunnel, excavation machines, and the target of the present study.

Chapter two covers a brief review of the available literature related to the tunnels, different excavation tunneling methods. This includes the properties, advantages, and disadvantages of each method of drilling methods, in addition to the use of each method.

This chapter also presents a review about previous studies that deal with the effect excavation machine on the adjacent soil during drilling and review about methods to predict the behavior of stresses and settlement of soil.

Chapter three presents the methodology of the numerical model for tunneling constructed stages and procedures for building model. This chapter also shows the data of the investigation of field and laboratory for area limited.

Chapter four includes the presentation of test results and their discussions while chapter five reviews a summary of the main conclusions and recommendations for future work.

